

SUBSTITUTE SPECIFICATION**Electromagnetic Ultrasonic Transducer****~~Background of the Invention~~****BACKGROUND OF THE INVENTION**Field of the Invention

[0001] _____ The present invention relates to an electromagnetic ultrasonic transducer for coupling[-] media[-] free generation and/or reception of ultrasonic waves in the form of linearly polarized transverse waves into-a, ~~and~~ respectively from, a workpiece having at least one unit that converts the ultrasonic waves inside the workpiece. The unit has a coil arrangement for generating, ~~respectively and/or~~ detecting, a high-frequency (HF) magnetic field and a premagnetizing unit for generating a quasi-static magnetic field which superimposes the HF magnetic field in the work piece, with the coil arrangement being ~~disposed in a torus[-]shaped manner~~ on at least one partially toroidal or U-shaped ~~designed~~ magnetic core which has two front ends which can each be turned to face the workpiece.

[0002] _____ ~~Such type~~ These ultrasonic probes permit generating and receiving linearly polarized transverse waves, which preferably are irradiated under the probe perpendicularly into the workpiece, ~~respectively and~~ are received from this direction and oscillate preferably perpendicular to their propagation direction. Technical fields of application of such type ultrasonic probes are, for example, nondestructive examination of electrically conductive workpieces for material flaws, such as for example cracks, in particular crack-like flaws oriented parallel to the polarization direction of the ultrasonic waves and perpendicular to the propagation direction, as well as other processes based on ultrasonic velocity and polarization, such as for example measuring voltage or, in particular, measuring thickness.

~~Prior Art~~ Description of the Prior Art

[0003] _____ The coupling[-] media[-] free electromagnetic probes known ~~from the state of in~~ the art convert electromagnetic field energies into the elastic energy of an ultrasonic wave and inversely. The conversion mechanism is based on the

interaction between the electromagnetic field and an electrically conducting material that ~~moreover~~ also has a static magnetic field or a quasi-static magnetic field applied from the outside which passes through the conducting material. The term "quasi-static" magnetic field comprises, in addition to the actual static magnetic field, which for example can be generated by means of permanent magnets, also low-frequency magnetic fields, whose alternating frequency is much lower than the high frequency with which the coil arrangement is operated to generate high-frequency fields.

[0004] In order to excite ultrasonic waves inside an electrically conducting workpiece, at least one part of the high-frequency magnetic field, whose frequency range lies within the ultrasonic frequency range, generated by the high-frequency coil arrangement, is coupled into the workpiece, thus inducing eddy currents at skin depth, which if superimposed by on the "quasi-static" magnetic field, generate ultrasonic waves due to the Lorentz forces or magnetostrictions occurring inside the workpiece.

[0005] Detection of ultrasonic waves occurring inside the workpiece occurs inversely by detection of the electrical voltage induced inside the coil arrangement resulting from high-frequency fields which for their part are generated by the motions of electric charges, due to the ultrasonic waves, in the workpiece inside the "quasi-static" magnetic field.

[0006] All prior art electromagnetic ultrasonic transducers are based on ~~the common goal of development to optimize~~ optimizing measuring sensitivity and, related thereto, the signal amplitudes ~~in of~~ both the transmission signal ~~as well as~~ and in the reception signal that can be generated with the coil arrangements. The ~~aim goal~~, on the one hand, is to design the coupling mechanism with which the generated and to-be-detected high-frequency fields are coupled into and out ~~between~~ of the ultrasonic transducer and the workpiece as loss-free as possible and, on the other hand, to select the field strength of the quasi-static magnetic field as large as possible, which is decisive for generating and detecting ultrasonic waves.

[0007] German Patent DE 42 23 470 C2 describes a generic electromagnetic probe for vertical acoustic irradiation of linearly polarized transverse waves, in which

the high-frequency magnetic fields are coupled into and out of in a most efficient manner between the probe and the workpiece without, as is the case with many other probes, placing the transmission and reception coils, (usually designed as high-frequency air coils), directly on the surface of the workpiece. But rather the electromagnetic probe of ~~figure~~ Fig. 2 described in this printed publication is provided with a half-open toroidal tape core 1, made commercially of amorphous tape material, around which a transmission coil 41 and a reception coil 42, respectively, are wound. The front ends 2 of the half-open toroidal ~~tape~~ core 1 act as coupling areas for the high-frequency magnetic fields and can be placed in ~~a suited manner~~ on the surface of the workpiece 7 ~~to-be-examined workpiece 7~~. The high-frequency magnetic fields generated by the high-frequency transmission coil arrangement 41 reach, via the front ends 2 of the toroidal ~~tape~~ core 1, into the workpiece 7 and are able to induce ~~close to the surface~~ eddy currents 8 at skin depth inside the workpiece 7.

[0008] The quasi-static magnetic field oriented perpendicular to the surface of the workpiece 7 required for sound conversion is generated by means of two permanent magnets 6 of the same name and conveyed to the material surface of the workpiece 7. The premagnetizing unit required for producing the “quasi-static” magnetic field that is oriented perpendicular to the surface of the workpiece is located inside the open part of the toroidal ~~tape~~ core 1. With this arrangement, ultrasonic waves with a propagation direction A perpendicular to the surface of the workpiece and an oscillation plane S perpendicular thereto develop inside the workpiece.

[0009] German Patent DE 41 30 935 A1 describes a probe device comparable to this arrangement. However, in this probe device the transmission and reception coil arrangement lies directly on the surface of the workpiece ~~to-be-examined workpiece~~, which ~~harbors~~ has the danger of coil wear.

[0010] German Patent DE 195 43 482 A1 describes a device for testing ferromagnetic materials, preferably in the form of pipe lines. However, this device has a components setup that differs from the state of the art described in detail in the preceding and on which the following is based.

Summary of the Invention

SUMMARY OF THE INVENTION

[0011] Based on the aforementioned state of the art, the object of the present invention is to further develop a generic an electromagnetic ultrasonic transducer which efficiently generates in such a manner that the efficiency with which the ultrasonic waves with an improved are generated and detection sensitivity are decisively improved compared to the prior art ultrasonic transducers. In particular, the object is to dispose the coil arrangement is disposed at a distance from the surface of the workpiece in order to be able to prevent rule-out mechanical impairment of the coil arrangement. Moreover, the further developed ultrasonic transducer is to permits generating horizontally polarized ultrasonic waves.

[0012] A key element of the present invention is to further develop an electromagnetic ultrasonic transducer for coupling~~[-]~~ media~~[-]~~ free generation and/or reception of ultrasonic waves in the form of linearly polarized transverse waves into, and respectively from, a workpiece, having at least one unit which converts the ultrasonic waves inside the workpiece and which is provided with a coil arrangement for generating, respectively and/or detecting, a high-frequency magnetic field as well as a premagnetizing unit for generating a quasi-static magnetic field which is superimposes superimposed upon the high-frequency magnetic field in the workpiece, with the coil arrangement being disposed in a torus-shaped manner on at least one partially toroidal or U-shaped magnetic core, which has two front ends that can be turned to face the workpiece, in such a manner so that the front ends of the magnetic core, that can be turned to face the workpiece, are connected directly or indirectly to a magnetic flux guide piece which has a surface facing the workpiece and which connects the front ends with one another.

[0013] Providing such a type flux guide piece connecting the front ends of a magnet core, preferably designed as a toroidal tape core, with each other, permits, in particular, coupling~~[-]~~ in the high-frequency magnetic fields generated by the coil arrangement most efficiently into the workpiece in order to be able, in this manner, to generate very distinctive eddy currents at skin depth. For this purpose, the flux guide piece has a surface which is preferably designed conforms with the surface of the workpiece thereby permitting, preferably contour-matching, contacting of the flux

guide piece and the workpiece. In a preferred embodiment, the flux guide piece is formed as a rectangular rod with a plane surface facing the workpiece. The plane surface can be placed flush on an equally plane formed workpiece surface without any coupling media. The surface of the flux guide piece facing the workpiece can, of course, be produced, depending on the curvature behavior of the to-be-examined workpieces, in a surface mold matching the contour of the workpiece. If the electromagnetic ultrasonic transducer is to be, for example, utilized preferably for examining cylindrical workpiece surfaces, the flux guide piece connecting the front ends of the toroidal tape-cores is formed corresponding to the nature of the contour.

[0014] In addition to ~~optimized coupling in~~ optimize coupling of the high frequency magnetic field into the workpiece surface by means of the flux guide piece, the flux guide piece is also able to couple in the quasi-static magnetic field almost without losses into the workpiece. For this purpose, in a typical preferred embodiment, the premagnetizing unit for generating the quasi-static magnetic field ~~has the form of~~ is a permanent magnet, which is disposed directly on the flux guide piece between the front ends of the toroidal tape-core, which projects beyond the permanent magnet. In this case, the flux guide piece acts as a ~~type~~-concentrator for the quasi-static, ~~respectively and~~ permanent magnetic field.

[0015] In order to prevent eddy currents from developing inside the flux guide piece, it is advantageous to make the flux guide piece out of an electrically nonconductive carrier material into which a matrix-like ~~of~~ soft magnetic particles are introduced. Alternatively, a stack-shaped arrangement of soft magnetic transformer metal sheets can also effectively prevent eddy currents from developing inside the flux guide piece.

[0016] In addition to the ~~aforedescribed invented design of an~~ electromagnetic ultrasonic transducer whose partially toroidal or U-shaped magnetic core projects beyond a single magnetic flux guide piece, with the front ends of the magnetic core being closely connected to the single flux guide piece, a second, alternative ~~invented~~ preferred embodiment of an electromagnetic transducer is provided with at least two flux guide pieces disposed side by side in parallel which are connected to each other in a bridge-like manner by at least two partially toroidal or U-shaped magnetic cores

via their respective front ends. The magnetic cores are ~~situated~~ disposed at a distance from each other at the opposite end regions of the rod-shaped flux guide pieces. This manner of construction permits placing the premagnetizing unit, preferably in the form of a permanent magnet arrangement, between the two magnetic cores in a longitudinal direction of the two flux guide pieces without the magnetic cores, preferably ~~designed as toroidal tape cores~~, spanning them as with ~~is the case in the~~ previously ~~aforedescribed~~ preferred embodiment. As a result, the possibilities ~~in~~ of scaling the dimensions of the permanent magnet arrangement are practically unlimited, permitting enlarging the magnetic field strength accordingly.

[0017] In addition to the simplest preferred embodiment of the magnetic core in the form of a toroidal ~~tape~~ core wound with at least one coil arrangement, also feasible are magnetic cores with an M-shaped magnetic cross section each having three free-ending front ends. Compared to the preceding electromagnetic ultrasonic transducer arrangement, with such type magnetic cores, three parallel adjacent magnetic flux guide pieces can be connected in a bridge-like manner.

[0018] As described in detail further on herein with reference to the following preferred embodiments, linearly polarized transverse waves can be generated inside the workpiece by ~~suited combination of a~~ multiplicity of the ~~aforedescribed~~ ultrasonic transducers and triggering of the coil arrangements placed on the magnetic cores in a toroidal manner. In particular, corresponding multiple arrangements permit generating vertically or horizontally linearly polarized transverse waves.

[0019] For this purpose the electromagnetic ultrasonic transducers according to the present invention as previously ~~described~~, ~~in the beginning~~ can be placed side by side in a multiple arrangement in order to obtain, on the one hand, a large as possible a transmitting and receiving aperture and, on the other hand, to obtain, by means of phase-controlled high-frequency excitation of the individual coil arrangements, a selectively settable irradiation characteristic for the ultrasonic waves that can be coupled into the workpiece. As will be described further on herein, such type arrangements are suited for a phased array arrangement for generating horizontally polarized transverse waves (shear horizontal waves) whose propagation

direction can be selectively set, which includes with reference to the normals of the workpiece surface a variable angle between 0° and 90°.

Brief Description of the Invention

BRIEF DESCRIPTION OF THE INVENTION

[0020] The present invention is made more apparent in the following with reference to the accompanying drawings by way of example without the intention of limiting the scope or spirit of the inventive idea invention.

[0021] Fig. 1_—shows an electromagnetic ultrasonic transducer having a single flux guide piece;_i

[0022] Fig. 2_—shows a state-of-the-art electromagnetic ultrasonic transducer;_i

[0023] Fig. 3_—shows an arrangement of a multiplicity of single electromagnetic ultrasonic transducers according to the embodiment of ~~figure~~ Fig. 1;_i

[0024] Fig. 4_—shows a schematic representation of an ultrasonic wave field generated inside a workpiece by the arrangement according to ~~figure~~ Fig. 3;_i

[0025] Fig. 5_—shows an electromagnetic ultrasonic transducer having two flux guide pieces which are spanned in bridge-like manner by two semi-toroidal magnetic cores;_i

[0026] Fig. 6_—shows a multiplicity of electromagnetic ultrasonic transducers according to ~~figure~~ Fig. 5;_i and

[0027] Fig. 7_—shows a cross section of M-shaped magnetic cores_i which each span in a bridge-like manner three magnetic flux guide pieces.

DETAILED DESCRIPTION OF THE INVENTION

Ways to Carry Out the Invention, Commercial Applicability

[0028] ~~Figure Fig. 1~~ shows the simplest preferred embodiment of an electromagnetic ultrasonic transducer designed according to the present invention, in which ~~the a~~ partially toroidally designed magnetic core is ~~designed~~ configured as a halved half toroidal tape-core 1 whose with two front ends 2 are directly connected to a rod[-] shaped flux guide piece 3 having ~~designed with a~~ rectangular cross section. Wound about the halved half toroidal tape-core 1 in a torus[-] shaped manner is a coil arrangement 4, which has two connections ~~connecting contacts~~ 5. Provided directly on the surface 31 of the flux guide piece 3 is a premagnetizing unit 6, which, in the preferred embodiment, is ~~designed as a~~ permanent magnet and has a north pole as indicated. The toroidal tape-core 1 projects completely over the permanent magnet 6. Also only indicated is the workpiece 7 to be examined with the aid of the electromagnetic ultrasonic transducer arrangement and on whose workpiece surface 71, the flux guide piece 3 with its surface 32 facing the workpiece 7 can be placed, preferably with a matching its contour. In this manner, the magnetic field generated by means of the permanent magnet 6 enters the workpiece 7 perpendicularly through the flux guide piece 3 via the workpiece surface 71. Alternatively to the embodiment of the premagnetizing unit in the form of a permanent magnet 6, as ~~depicted illustrated~~ in figure ~~Fig. 1~~, it is ~~feasible to design~~ the premagnetizing unit may be in the form of an electromagnet whose field lines enter the workpiece perpendicular to the workpiece surface in the same manner as in the arrangement depicted in figure ~~Fig. 1~~. However, it is also possible to position an electromagnet so ~~in such a manner~~ that the magnetic field generated by the electromagnet enters the workpiece parallel to the workpiece surface. The effects related to such a type magnetic field alignment ~~is~~ are described hereinafter ~~in the further on herein~~.

[0029] ~~The~~ electromagnetic ultrasonic transducer shown in figure ~~Fig. 1~~ should be viewed as an electromagnetic ~~line~~ transducer which can be operated both as an ultrasonic transmitter and an ultrasonic receiver. When transmitting, the connecting connection contacts 5 are connected to a high-frequency generator, and when receiving ~~however the connecting connection~~ contacts 5 are connected to a corresponding amplifier and a downstream evaluation unit. Of course, two separate

coil arrangements, ~~of which with one acts acting as~~ a transmission coil and the other ~~acting as~~ a reception coil, can also be provided along a single halved-half toroidal tape-core.

[0030] Due to the large area contact between the upper-lower side 32 of the flux guide piece 3 and the workpiece surface 71 of the workpiece 7, the high-frequency magnetic fields conveyed in the longitudinal direction of the flux guide piece 3 couple into the workpiece 7 along the entire longitudinal extension of the flux guide piece 3 and generate intensive eddy currents at skin depth. These eddy currents, ~~for their part,~~ interact with the quasi-static magnetic field passing through the workpiece surface 71 and generate, due to the developing Lorentz forces and magnetostrictions, ultrasonic waves with a frequency corresponding to the alternating frequency of the high-frequency magnetic fields. Due to the close contact between the flux guide piece 3 and the workpiece surface 71, a higher magnetic flux is generated inside the workpiece 7 than is the case with the hitherto known electromagnetic ultrasonic transducers, for example as ~~depicted-illustrated~~ in figure Fig. 2. In this manner, the ~~effectivity and the effectiveness of~~ generation of the ultrasonic waves ~~and as well as the sensitivity in of~~ the reception case can be increased considerably.

[0031] The preferred embodiment of an electromagnetic ultrasonic transducer shown in figure Fig. 1, in which the quasi-static magnetic field passes perpendicularly through the workpiece surface 71, permits generating linearly polarized transverse waves whose propagation direction is oriented perpendicular to the surface of the workpiece and has an oscillation plane oriented perpendicular to the propagation direction.

[0032] Selective excitation of so-called horizontally polarized transverse waves (shear horizontal waves) requires, in ~~an as such a~~ known manner, a premagnetizing unit, usually in the form of an arrangement of permanent magnets with an alternating polarity whose alternating magnetic fields superimpose a high-frequency magnetic field inside the workpiece. Figure Fig. 3 shows an arrangement designed according to the present invention, for generating horizontally polarized transverse waves, which, in the ~~depicted-illustrated~~ preferred embodiment, is provided with five parallel

electromagnetic line transducers arranged adjacent to each other according to the example shown in figure-Fig. 1. It is assumed that the coil arrangements 4, as indicated-illustrated in figure-Fig.3, on each of the singly depicted-illustrated ultrasonic transducers are designed for generating and as well as for receiving ultrasonic waves. If the electrical connections 5 of the individual coil arrangements 4 for transmitting and receiving are connected at to separate electronic channels of a high-frequency generator, respectively-and of a corresponding amplifier, and if the individual electronic channels are operated in a time-delayed manner in their triggering phase, a phased array arrangement which is able to generate and detect horizontally polarized transverse waves inside the workpiece - like a group radiator - can be realized-achieved with the arrangement depicted-illustrated in figure- Fig. 3. Adjacently disposed ultrasonic transducers operated with a magnetic flux directed in the opposite direction in the flux guide piece, thereby generating alternating developing-eddy current directions under the adjacent flux guide pieces. This causes , which lead to Lorentz forces directed in opposite directions and the related magnetostriction directions. and in In this manner generate-shear forces are generated to produce horizontally polarized transverse waves inside the workpiece.

[0033] Suited-Suitable selection of the phase-dependent triggering of the individual ultrasonic transducers disposed side by side in a row permits selectively setting the direction characteristic of the developing horizontally polarized transverse waves. in such a In this manner that the main propagation direction of the main lobe of the horizontally polarized transverse waves form an angle α , selectable from 0° to 90° as desired, with the surface normals of the surface of the workpiece. Figure Fig. 4 shows an illustrative sketch of a system for of generating horizontally polarized transverse waves with the aid of the ultrasonic wave arrangement depicted-illustrated in figure-Fig. 3. It is assumed that four ultrasonic transducers $S_1 - S_4$ are disposed side by side at a distance D from each other on the workpiece surface 71. A current pulse is applied to the individual ultrasonic transducers $S_1 - S_4$ at an interval of Δt in the aforedescribed manner. Due to the phase-delayed application of current to the ultrasonic transducers $S_1 - S_4$, horizontally polarized transverse waves develop inside the workpiece. These transverse waves have a main propagation direction that

forms with the normals of the surface of the workpiece an angle α , for which

$$\alpha = \sin(c_t \cdot \Delta t / D)$$

applies.

[0034] In the above equation c_t ~~stands~~ represents for the propagation velocity of the horizontally polarized transverse wave in the workpiece, ~~showing in~~ In this manner, ~~that~~ if all four ultrasonic transducers are triggered phase-synchronously, i.e. that is $\Delta t = 0$, α equals zero so that the horizontally polarized transverse waves are irradiated into the workpiece perpendicular to the surface of the workpiece. If the individual ultrasonic transducers are operated with a phase-delay of Δt , during which an ultrasonic wave, for example, reaches from an ultrasonic transducer S1 to the transducer S2, ~~that is~~ covers the distance D, the main lobe of the horizontally polarized transverse waves developing inside the workpiece forms an angle α of 90° with the normals ~~of~~ the surface of the workpiece. Depending on the choice of Δt , the main lobe can be ~~swung~~ varied as desired between 0° and 90° inside the workpiece.

[0035] The preceding description, which relates to a transmission operation, can be transferred inversely also to the reception of shear horizontal waves from a workpiece.

[0036] Another embodiment of an electromagnetic ultrasonic transducer designed according to the present invention is shown in ~~figure~~ Fig. 5. The transducer is provided with two magnetic flux guide pieces 3 , and $3'$ disposed in parallel at a distance from each other. The upper sides 32 , and $32'$ of the two magnetic flux guide pieces 3 , and $3'$ are connected to the front ends of the two semi-circular-shaped toroidal ~~tape~~ cores 1 , and $1'$. The two magnetic flux guide pieces 3 , and $3'$ are thus connected to each other in a bridge-like manner by the toroidal ~~tape~~ cores 1 , and $1'$. Moreover, the preferred embodiment shown in ~~figure~~ Fig. 5 has two counter pole permanent magnets 6 , and $6'$ resting on the respective magnetic flux guide pieces 3 , and $3'$. Triggering the coil arrangements of the individual toroidal ~~tape~~ cores 1 , and $1'$ occurs in such a manner that dynamic magnetic fields directed in opposite directions are generated in the magnetic flux guide pieces 3 , and $3'$, ~~leading to causing~~ causing eddy

currents in the workpiece, which are oriented perpendicular to the longitudinal extension of the magnetic flux guide pieces 3, and 3' as well as in opposite directions. Due to the opposite poled permanent magnets 6, and 6', shear forces directed in the same direction develop at skin depth inside the workpieces under the flux guide pieces, thereby creating linearly polarized transverse waves with ultrasonic waves propagating perpendicularly to the surface of the workpiece. Therefore, the arrangement shown in ~~figure~~ Fig. 5 can be ~~viewed as~~ considered to be a normal probe for generating and detecting linearly polarized transverse waves having a large aperture, comparable to the arrangement which has only a single electromagnetic line transducer according to the type of setup of the preferred embodiment shown in ~~figure~~ Fig. 1.

[0037] ~~Figure~~ Fig. 6 shows an arrangement of three normal probes disposed side by side according to the basic setup of the ultrasonic transducer depicted in ~~figure~~ Fig. 5. The three normal probes N disposed side by side are switched with their respective high-frequency coils 4 ~~in such a manner so~~ that in the adjacent flux guide pieces, the direction of the dynamic magnetic fields are oriented in opposite directions, ~~i.e. that is~~ there is a phase difference of 180° between the directly adjacent high-frequency magnetic fields. Due to the ~~in this manner-oriented~~ magnetic flux of the dynamic magnetic fields being directed in opposite directions, ~~in transmission the~~ eddy currents which are oriented perpendicular to the direction of the dynamic magnetic fields are coupled into the surface of the workpiece. If a uniform static magnetic field is superimposed, the eddy currents j generate Lorentz forces F_l directly under the respective flux guide pieces 3. The Lorentz forces F_l under the adjacent flux guide pieces are directed in opposite directions and therefore produce shear forces inside the workpiece thereby generating shear horizontal transverse waves. The coil wavelength, which corresponds to the half oscillation wavelength of the SH wave, is determined by the distance between the directly adjacent flux guide pieces. The irradiation direction of the shear horizontal waves is oriented perpendicular to the individual flux guide pieces 3, indicated by the arrows A directed in opposite directions according to ~~figure~~ Fig. 6.

[0038] ~~The arrangement-embodiment~~ shown in ~~figure~~ Fig. 6 comprises, in particular, ~~also a selective use of a large-area unipolar magnet 6 which is decisively~~

able to suppress the disturbing Barkhausen noise in the region of the individual transducer elements.

[0039] ~~Figure Fig. 7 shows an arrangement embodiment very similar to the arrangement embodiment of figure Fig. 6 for generating shear horizontal waves. Contrary In contrast to figure Fig. 6, in figure Fig. 7, the toroidal tape-core segments 1' are designed in the form of m-shaped coil cores, with two m-shaped coil cores each being provided with three flux guide pieces 3, 3', and 3". The M shaped cores 1' include parallel pieces 8 with face front ends 2' and are joined by connection parts 9. The coils arrangements provided around the coil cores 1 are switched so in such a manner that high-frequency magnetic fields directed in opposite directions develop in the longitudinal direction of the flux guide pieces located adjacent to each other in parallel. Superimposition of the high-frequency magnetic fields by a static magnetic field generated by the a unipolar permanent magnet 6, which completely covers the three normal probes N, and oriented perpendicular to the surface of the workpiece over the high-frequency magnetic fields leads to causes eddy currents directed in opposite directions inside the workpiece under the directly adjacent flux guide pieces, thereby These eddy currents evoking produce Lorentz forces which are also directed in opposite directions and, for their part, are responsible for the shear forces required to generate horizontally polarized transverse waves.~~

[0040]_____List of References

1 toroidal ~~tape~~-core

2 front end

3 flux guide piece

31, and 32 surfaces of the flux guide piece

4 coil arrangement

41 transmission coil

42 reception coil

5 electrical contacts

6 permanent magnet

7 workpiece

8 eddy current

Abstract

~~Disclosed is an~~ An electromagnetic ultrasonic transducer for coupling-media-free generation and/or reception of ultrasonic waves in the form of linearly polarized transverse waves in a, ~~respectively and~~ from a workpiece is disclosed, having at least one unit which converts the ultrasonic waves inside the workpiece and which is provided with a coil arrangement for generating, ~~respectively and/or~~ detecting a high-frequency magnetic field and as well as with a premagnetizing unit for generating a quasi-static magnetic field which superimposes ~~upon the~~ high-frequency magnetic field in the workpiece, ~~with the~~ The coil is arrangement being disposed in a torus-shaped manner on at least one partially toroidal or U-shaped magnetic core, having ~~which each has two front ends which can be turned to face the workpiece.~~

~~The invention is distinguished in that the~~ The front ends of the magnetic core, which can be turned to face the workpiece, are connected directly or indirectly to a magnetic flux piece which has a surface ~~which faces~~ facing the workpiece and ~~which connects~~ connecting the front ends with each other.